












VORTEX 120

**Portal Turnstile, full-height,
120° partition angle,
acrylic panels**

Particularly suitable for well-frequented entrances with entry and exit operation in indoor areas in public baths and leisure facilities and in factory security as well as in architecturally sophisticated buildings. The fully transparent design fits in sleekly to any architectural design.



- ✓ Transparent design for the architecturally sophisticated interior
- ✓ 120° partition angle, acrylic panels
- ✓ Compact design
- ✓ Bi-directional operation
- ✓ Input direction can be changed
- ✓ Durable quality
- ✓ LOGITURN® Drive Unit
- ✓ Maintenance-free mechanics



Description

The motor-driven full-height vertical turnstile VORTEX with 120° partition angle of the barrier element is made entirely of stainless materials and is particularly suitable for the installation of barriers at area-separating access points in office buildings as well as in swimming pools and leisure facilities.

Easy to service: The lockable cover and the drive and locking unit accessible from above make it particularly easy to service and commission.

Versions

6VOX21E3A: VORTEX 120

Optional equipment

- 22197-N** RAL coating
- 2PV12-N** Light barrier activation
- 8P416-N:** USV 2,2 Ah

Application areas

- Baths and spas
- Offices and main entrances
- Plant protection
- Utilities

Suitable products

- 21501:** Reader stand column 154 mm round
- 21695:** Reader stand column 140x140 mm squared
- 21094:** Pedestrian gate ECCO 2100 with acrylic filling
- 21130MH:** Safety glass panel 10 mm

Technical features

Power supply::	24 V
Consumption:	50 VA
Storage temp.:	-40°C - +50°C
Operating temp.:	-20°C - +40°C
Passage width:	705mm
Outside diameter:	1.579mm
Height / Passage:	2.273mm / 2.073mm
Weight:	350kg
Material:	Housing aluminum powder coated, deflector + rotating column CrNi steel 1.4301, blocking elements acrylic glass
Communication:	floating contacts, logic inputs via optocouplers

